


Blackiro

Art no: HV-NXC3158



Art no:	HV-NXC3158
Size:	7-12
Materials:	HPPE, Nitrile
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



Properties

Thin and seamless cut resistant glove (Level F) with the highest level of cut protection. Reduces the risk of injury when in contact with sharp edges and even bladed tools. Equipped with a micro foam nitrile coating in the palm and over the fingertips. The glove is abrasion resistant, oil resistant with an excellent grip in dry, wet or oily conditions. Very comfortable glove with great breathability and firm fit.

Material information

Knitted cutter glove in the highest level (Level F). Nitrile Coating in the innerhand with Sandy Grip technology.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional test) P if approved.

Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



abcdef

