

PRODUCT DATA SHEET



Smooth

Art no: PR-500



Art no:	PR-500
Size:	7-11
Materials:	PU, Quick Dry, Lycra, Terrycloth
Packaging:	12/120
Standard:	EN420, EN388:2016
Category:	II



CATEGORY: II

EN420



EN388:2016



1111X



Properties

Extremely light premium glove in slim-fit design for a superior fit. Elastic and durable premium PU on the inner hand for an excellent grip. Fingertip reinforcements in PU. Sewn in elastic Quick Dry fabric on the upper hand with contrast seams. Elastic Lycra between fingers. Elastic seams at the wrist for a better fit. Pull tab on the inside of the cuff to quickly take on or off the glove. Soft terry cloth on the upper thumb for wiping the forehead. Adjustable cuff with a velcro lock. Extremely comfortable glove for ultimate precision and tactile feeling.

Material information

The gloves are sewn in smooth PU, upper hand in Quick Dry, Lycra fourchettes, Terrycloth at thumb.

Technical facts: Intermediate design (category II)

For areas of specific risks, i.e. mechanical risks. These products will have been CE type tested against European EN388:2016 test methods and certified by a notified body. The testing is done for abrasion resistance, cut resistance, tear resistance, puncture resistance, extended cut resistance and impact protection. The maximum score for each level are; abrasion 4, cut resistance 5, tear resistance 4, puncture resistance 4, extended cut resistance F (X if not applicable) and impact protection (optional) P if approved. Evaluate the importance of each of the properties and how it applies to you as a user.

How to read the pictogram:

EN388:2016



a b c d e f

abrasion resistance
cut resistance
tear resistance
puncture resistance
extended cut resistance
impact protection (optional)

Soft Touch AB

Postal adress Gamla Alingsåsvägen 24, 433 38 Partille, Sweden

Phone: +46 (0)31-548050 Fax: +46 (0)31-531005 Email: info@softtouch.se Website: www.softtouch.se